

NAME

CURLOPT_HTTPPOST – specify the multipart formpost content

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_HTTPPOST,  
    struct curl_httppost *formpost);
```

DESCRIPTION

Tells libcurl you want a multipart/formdata HTTP POST to be made and you instruct what data to pass on to the server in the *formpost* argument. Pass a pointer to a linked list of curl_httppost structs as parameter. The easiest way to create such a list, is to use *curl_formadd(3)* as documented. The data in this list must remain intact until you close this curl handle again with *curl_easy_cleanup(3)*.

Using POST with HTTP 1.1 implies the use of a "Expect: 100-continue" header. You can disable this header with *CURLOPT_HTTPHEADER(3)*.

When setting *CURLOPT_HTTPPOST(3)*, it will automatically set *CURLOPT_NOBODY(3)* to 0.

DEFAULT

NULL

PROTOCOLS

HTTP

EXAMPLE

```
/* Fill in the file upload field. This makes libcurl load data from  
the given file name when curl_easy_perform() is called. */
```

```
curl_formadd(&formpost,  
    &lastptr,  
    CURLFORM_COPYNAME, "sendfile",  
    CURLFORM_FILE, "postit2.c",  
    CURLFORM_END);
```

```
/* Fill in the filename field */
```

```
curl_formadd(&formpost,  
    &lastptr,  
    CURLFORM_COPYNAME, "filename",  
    CURLFORM_COPYCONTENTS, "postit2.c",  
    CURLFORM_END);
```

```
/* Fill in the submit field too, even if this is rarely needed */
```

```
curl_formadd(&formpost,  
    &lastptr,  
    CURLFORM_COPYNAME, "submit",  
    CURLFORM_COPYCONTENTS, "send",  
    CURLFORM_END);
```

AVAILABILITY

As long as HTTP is enabled

RETURN VALUE

Returns CURLE_OK if HTTP is enabled, and CURLE_UNKNOWN_OPTION if not.

SEE ALSO

CURLOPT_POSTFIELDS(3), CURLOPT_POST(3),